GASPARDO

ROW CROP CULTIVATORS







GASPARDO

Product range



All models are available with 45 or 75 cm inter-row distance (adjustable to 50-60-65 or 70). Transformation can take place after purchase, through a specific kit.

HL \rightarrow 4 to 12 rows fix frame.



HP \rightarrow 4 to 6 rows folding frame with transport width of 2.5 m



HS → 6 to 12 rows, hydraulic folding frame with transport width of 2.5 m. High hopper capacity (max 950 liters), pneumatic distribution on side rows and wings with automatic disengagement



 $HR \rightarrow 12$ to 18 rows, suitable for large farms. Available with independent or integrated trolley



GASPARDO

SARCHIATRICI: HL - HP - HS - HR

Strong points: HS element common on the entire range

- ✓ high ground clearance to avoid any damages to the crops
- ✓ reinforced spring (12 mm) higher performance and wear resistance (OPT tine with tungsten protection)
- ✓ self lubricating bushings, low maintenance need
- √ no tangling thanks to springs position
- √ all wheels on bearings
- ✓ easy unlock of elements to switch transport to working mode from the tractor cab
- ✓ side protections can be excluded
- ✓ fertilizing agent distribution through MiniMax





IIRB Seminar 2011 1

GASPARDO

New Element

Higher ground clearance to avoid any damages to crops. From 60 to 70 cm depending on crop and machine setup. The 12mm spring guarantees higher performance and better wear resistance. **LONG LIFE** with tungsten protection makes tool life 2 times longer, thus reducing time waste.




Springs are better spaced and positioned to guarantee an optimal flow and avoid clogging.

Accessories



GASPARDO

Configurations for BETTERave





3MD → multipurpose element. Discs prevent plant damages



 $3MP \rightarrow$ multipurpose element. Side protections let the machine work even through early crops thanks to the soil containing effect.



3MDD → multipurpose element, disc protections are suitable for working on stony soils or with many weeds.





Optional load spring








Loading auger



External rows disengagement





HS version is available with the stainless steel hopper by 950 l suitable for big bags.



IIRB Seminar 2011 3